

Pioneer 700-2

Honda's Pioneer™ 700-2 sets the standard as the ultimate in hard-working, hard-playing side-by-sides. With the ability to carry two people and a load of gear and supplies, this side-by-side is ideal for reaching those hard to get to places.



THE SPECS Pioneer 700-2

Engine Type	675cc liquid-cooled OHV single-cylinder four-stroke
Bore and Stroke	102.0 x 82.6mm
Compression Ratio	9.2:1
Induction	Fuel Injection (PGM-FI), 40mm throttle body
Ignition	Full-transistorised with electronic advance
Clutch	Automatic
Transmission	Automotive-style with hydraulic torque converter, three forward gears and reverse. Three drive modes include 2WD, 4WD and 4WD with differential lock.
Drive	Direct front and rear driveshafts
Dimension	2,915mm x 1,524mm x 1,971mm (LxWxH)
Wheelbase	1,950mm
Ground Clearance	267mm
Turning Radius	4.5m
Fuel Capacity	30 litres, including 4.5 litres reserve
Front Tyre	25 x 8-12 inch
Rear Tyre	25 x 10-12 inch
Front Suspension	Independent double-wishbone; 200mm travel
Rear Suspension	Independent double-wishbone; 230mm travel
Front Brake	200mm hydraulic discs
Rear Brake	170mm hydraulic disc
Towing Capacity	680kg
Tilt Bed Capacity	453kg
Max Weight Capacity	650kg*
Kerb Weight	574kg
Warranty Period	36 months

*Any load limits apply to standard equipment only. Modifying your ATV or SXS, using non-standard equipment, or riding on terrain that is not flat and smooth could further reduce these limits.



*Overseas model shown.