

TRX420TM1

With an impressive list of features these mid-sized workhorses boast maximum durability and excellent handling performance.



THE SPECS TRX420TM1

Engine Type	420cc liquid-cooled OHV longitudinally mounted single-cylinder 4-stroke
Bore and Stroke	86.5 x 71.5mm
Carburation	Keihin 34mm throttle-body fuel-injection
Ignition	Full transistor with electronic advance
Starter	Electric with auxiliary recoil standard
Clutch	Automatic / Centrifugal
Transmission	5-speed with reverse
Drive	Direct rear driveshaft
Dimension	2,103mm x 1,204mm x 1,174mm (LxVxH)
Wheelbase	1,268mm
Seat Height	856mm
Ground Clearance	183mm
Turning Radius	2.8m
Fuel Capacity	14.7 litre (4.9 litre reserve)
Front Tyre	24 x 8-12 inch
Rear Tyre	24 x 10-11 inch
Front Suspension	Independent double-wishbone; 170mm of travel
Rear Suspension	Swingarm with single shock; 170mm of travel
Front Brake	Dual hydraulic discs, 190mm
Rear Brake	Sealed mechanical drum, 160mm
Max Weight Capacity	220kg*
Kerb Weight	261kg
Warranty Period	36 months

*Any load limits apply to standard equipment only. Modifying your ATV or SXS, using non-standard equipment, or riding on terrain that is not flat and smooth could further reduce these limits.



*Overseas model shown.