

TRX500FM2

Honda's next generation TRX500FM2; complete with revised Electric Power Steering, will continue to hold its reputation as a hard-working partner.



THE SPECS TRX500FM2

Engine Type	475cc liquid-cooled fuel injected OHV longitudinally mounted single-cylinder 4-stroke
Bore and Stroke	92.0 x 71.5mm
Carburation	Programmed Fuel Injection (PGM-FI), 36mm throttle body
Ignition	Full transistorised with electronic advance
Starter	Electric with auxiliary recoil
Clutch	Automatic / Centrifugal
Transmission	5-speed with reverse
Drive	Direct front and rear driveshafts with TraxLok® and locking front differential
Dimension	2,103mm x 1,204mm x 1,219mm (LxWxH)
Wheelbase	1,268mm
Seat Height	869mm
Ground Clearance	190mm
Turning Radius	3.2m
Fuel Capacity	14.7 litre (4.9 litre reserve)
Front Tyre	25 x 8-12 inch
Rear Tyre	25 x 10-12 inch
Front Suspension	Independent double-wishbone; 185mm of travel
Rear Suspension	Swingarm with single shock; 185mm of travel
Front Brake	Dual hydraulic 190mm discs
Rear Brake	Sealed 160mm mechanical drum
Towing Capacity	385kg
Carrier Capacity	40kg (front) 80kg (back)
Max Weight Capacity	250kg*
Kerb Weight	293kg
Warranty Period	36 months



*Any load limits apply to standard equipment only. Modifying your ATV or SXS, using non-standard equipment, or riding on terrain that is not flat and smooth could further reduce these limits.



*Overseas model shown.